

technical information

#8801



"GREEN"
Coating
Products

ProTek - BMPRIME™

ELASTOMERIC WATERPROOFING ACRYLIC
PRIMER SEALER for Roofs of
BUSES, TRUCKS, MOTOR HOMES & OTHER R.V.'S

PRODUCT DESCRIPTION

BMPRIME™ is a transparent white, 100% Acrylic Elastomeric, waterproof adhesive Primer Sealer designed as the Primer Sealer for **THERMCOTE/BM™** for Motor Home, Bus, Truck & other Recreational Vehicle Roofs. A waterborne, latex-based, high resin content formula that contains no fillers so that it waterproofs and provides excellent adhesion to most types of surface. A high resin content plus the addition of special adhesive chemicals enables **BMPRIME™** to waterproof, bond and seal the surface together preparing it for the application of **THERMCOTE/BM™**. Excellent penetrating characteristics enable **BMPRIME™** to permeate into the substrate providing a permanent bond to the finish coat. On non-porous substrates, the high resin content provides excellent adhesion to the surface then forming a tight bond to the finish coat. The bond that is formed between **BMPRIME™** and the **THERMCOTE/BM™** finish coat eliminates any possibility of moisture under the finish coat thus extending the coating's and roof's life considerably.

PRODUCT USES

BMPRIME™ is recommended for all Bus & Recreational Vehicle roofs. Roof Surface must be well drained and can not hold any ponding water. Excellent adhesion on wood, shakes, plywood, primed metal, galvanized, aluminum, tin, copper, asbestos, asphalt, urethane, polyester, styrofoam, fiberglass, rolled roofing, modified bitumen membranes, mineral surfaced roofing, concrete, masonry, and various other substrates.

- *Excellent Adhesion and Bonding*
- *Easy Application & Water Clean Up*
- *Safe for the Environment*

SURFACE PREPARATION

A primer sealer coat of **BMPRIME™** is required for the 7 Year Limited Warranty on the **THERMACOTE/BM™**, *Bus & Recreational Vehicle Coating System*. Prepare surface by thoroughly pressure washing with a water and chlorine solution using at least 1500 P.S.I. to remove

any previous coatings, dirt, grease, and other foreign materials, especially mold, mildew and algae. **BMPRIME™** will resist mildew growth but will not kill mildew already on the surface. Apply only to a sound, well-prepared surface. Prepare all rust and corrosion with **OXIPRIME™**, *Red Iron Oxide Primer Sealer* before the application of **BMPRIME™**. Patch any holes, cracks, valleys, etc., with **THERMAPATCH™**, *Waterproof Caulk and Sealant*. Tape and seal all seams with **POLYMESH™**, *Polyester Fabric Tape*.

APPLICATION PROCEDURE

Stir well before using. Do not thin. Use product as is. Do not apply when temperatures are below 45 degrees Fahrenheit or when humidity is very high. Do not apply when primer will be subjected to rain or heavy dew before it has had enough time to dry (approximately 4 to 6 hours). Drying time will vary depending on temperature, humidity & location. Apply using brush, roller or spray. Use at least a 1 gallon per minute piston type airless sprayer with a minimum tip size of .025. Spread uniformly. Wait at least 12 hours before applying **THERMACOTE/BM™**. It is necessary to topcoat **BMPRIME™** with **THERMACOTE/BM™** within 72 hours or surface may become contaminated.

CLEAN UP

Clean all tools immediately after use while still wet with warm soapy water.

PHYSICAL PROPERTIES

FINISH:Tacky Gloss
COLOR:Transparent White
DRY TIME: @77°C
DRY to TOUCH:4 to 6 Hours
RECOAT:12 Hours
FULL CURE:5 to 7 Days
VEHICLE TYPE:Copolymer Emulsion
SOLIDS by WEIGHT:42% +/- 2%
SOLIDS BY VOLUME:37% +/- 2%
GALLON WEIGHT:8.9lbs. +/- .3lbs.
SIZES:1Gal., 5Gal., 55Gal.

APPROXIMATE COVERAGE

75 to 150 sq.ft./gal./Coat

ProTek-USA, LLC 800-420-2998 Fax: 206-782-7532

Email: fbf@protek-usa.com

www.protek-usa.com